System 400

NEWTON 408 DECKDRAIN



Drainage Membrane for Decks and Flat Roofs

Rev 1.2 - 25 October 2016 PRODUCT CODE - M33

1. Identification of Chemical/Substance and Company

Trade name Newton 408 DeckDrain

Chemical composition HDPE

Company Address
 Newton Waterproofing Systems, Newton House, 17-19 Sovereign

Way, Tonbridge, Kent TN9 1RH

Web www.newtonwaterproofing.co.uk

Email address of the competent person

info@newtonwaterproofing.co.uk

Emergency telephone number +44 (0)1732 360 095

9am - 5pm (GMT) Mon - Fri

2. Hazardous Ingredients

Classification of the substance or mixture

According to Regulation CEE 1999/45, 67/548 and EC 1907/2006

polyethylene are belong to non-toxic

3. Composition

Main component of the substance HDPE

4. First Aid Measures

General information
 In case of persistent discomfort seek medical advice

Inhalation
 In case of irregular breathing or respiratory arrest use artificial respiratio.

Remove to fresh air and seek medical attention

Skin contact
 For thermal skin burns seek medical attention

Eye contact No specific measures. Seek medical advice if necessary

Ingestion No specific measures. Seek medical advice if necessary

5. Fire-Fighting Measures

EXTINGUISHING MEDIA

Suitable extinguishing agents
 Water, foam, dry chemical media

Special hazards arising from the substance or mixture

If product combusts, water, carbon dioxide, carbon monoxide (in case of oxygen deficiency) and other organic compounds can be produced. At the

beginning of the combustion (especially between 400°C-700°C)

it may generate also the Hydrocarbons and aldehydes (acetic acid and

crotonic acid)

NEWTON 408 DECKDRAIN

Drainage Membrane for Decks and Flat Roofs

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

No specific measures necessary

Environmental precautions
 Prevent the entry of HDPE granulate in the soil, surface water or

groundwater

7. Handling and Storage

Instructions for handling
 Should be noted when the product is handled and pneumatically

transported: VDI guideline 3673, 2263 (Germany). Fine particle material (< 0,125 mm) should not be allowed to accumulate, particularly when transported pneumatically. The product contains combustible polymers. The

relevant fire protection measures thus apply.

Measures against fire and explosion Not applicable

Storage
 Store away from smoking and flames

8. Exposure Controls / Personal Protection

General instruction on protection and hygiene

No further data

Personal protection
 No respirator, no goggles, no gloves, no further equipment required

9. Physical and Chemical Properties

Appearance Sheet and film

Color Diverse

Odor
 Essentially odorless

Melting Point ca. 130°C
 Density 956 kg/m³

Vapour pressure n.a.

Solubility in water Insoluble g/l

pH in g/IH20 n.a.

• Flash point +/- 340 °C

Explosive limits lower n. a. Vol. % upper n. a. Vol. %

10. Stability and Reactivity

Thermal decomposition
 With normal handling and storage the product is stable. At temperature

above 300°C some degree of thermal degradation will occur

Materials to avoid
 Strong oxidizing agents

Hazardous reactivity
 Not known

Hazardous decomposition products At ambient temperature – not known

NEWTON 408 DECKDRAIN

Drainage Membrane for Decks and Flat Roofs

11. Toxicological Information	
 Toxicology 	In our experience and according to information available to us the product is not harmful to health provided it is correctly handled and processed according to the given recommendations
12. Ecological Information	
• Ecology	Material is not readily biodegradable. Material is not expected to be harmful to aquatic organisms
13. Disposal Considerations	
Waste disposal	Dispose of in accordance with appropriate government and local regulations
14. Transport Information	
• Transport	The material is not hazardous for transport by sea, air and road/rail
15. Regulatory Information	
• Regulations	According to GeStoffV (Germany) from 1986.08.26 the material is not hazardous
16. Other Information	