

HydroCoat Tanking Slurry

Cementitious waterproof coating

Revision: 2.1 - 15th March 2023
Code: HSS-20



EN 1504-2: 2004

DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

1. PRODUCT NAME:

HydroCoat Tanking Slurry

2. ELEMENT ALLOWING IDENTIFICATION OF THE PRODUCT:

Name of product, date of manufacture, and batch number printed on the bag.

3. INTENDED USE(S):

Rigid coating for moisture control of concrete (2.2)

4. NAME, REGISTERED TRADE NAME, AND CONTACT ADDRESS:

Newton Waterproofing Systems
(a trading name of John Newton & Company Ltd.)
Newton House
17-19 Sovereign Way
Tonbridge
Kent
TN9 1RH
01732 360095
www.newtonwaterproofing.co.uk

5. AUTHORISED REPRESENTATIVE:

Not Applicable

6. AVCP:

System 4

7. ACCORDANCE WITH HARMONISED STANDARD:

EN 1504-2: 2004

HydroCoat Tanking Slurry

Cementitious waterproof coating

8. DECLARED PERFORMANCE:

Essential characteristics to BS EN 1504-2: 2004	Test Standard & Conditions	Result	Unit of measure
Water vapour permeability	EN ISO 7783-1	Class I SD < 5	m
Capillary water absorption	EN 1062-3	w < 0.1	kg/m ² . h ^{0.5}
Adhesion	EN 1542	≥ 1.0	N/mm ²
Reaction to fire	EN 13501-1	Euroclass A1	
Dangerous substances		Complies with 5.3	

9. DECLARATION

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the Newton Waterproofing Systems:

Name: Warren Muschialli - Managing Director



At: Newton Waterproofing Systems
Newton House
17-19 Sovereign Way
Tonbridge
Kent
TN9 1RH

On: 08 November 2022



HydroCoat Tanking Slurry

Cementitious waterproof coating

	 Newton Waterproofing Systems Newton House 17-19 Sovereign Way Tonbridge Kent TN9 1RH	HSS-20 EN 1504-2: 2004 Cementitious waterproof coating	
Essential characteristics to BS EN 1504-2: 2004	Test Standard & Conditions	Result	Unit of measure
Water vapour permeability	EN ISO 7783-1	Class I SD < 5	m
Capillary water absorption	EN 1062-3	w < 0.1	kg/m ² . h ^{0.5}
Adhesion	EN 1542	≥ 1.0	N/mm ²
Reaction to fire	EN 13501-1	Euroclass A1	
Dangerous substances		Complies with 5.3	

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.