

# Toughsheet Building Products Bespoke Data Sheet

## Manufacturer/ Supplier

- Frank Mercer & Sons  
Chequerbent Works  
Westhoughton  
Bolton  
BL5 3JF

## Product Out-line

- Recycled Polythene Sheeting for General purpose use

## Dimension and Tolerance

- Manufactured to Nominal  
Tolerances - Length - +/- 10%  
Width - +/- 10%  
Thickness - +/- 10%  
Elongation - + 400%  
Appearance - May contain particles/  
streaks, but holes are absent in film



## Storage

- Good code of practice must be used;  
Store in horizontal position not in direct sun light.

N/B - sun Light (UV) may degrade this product

## COSHH

- Toxicity - LD Polythene are chemically non-reactive, biologically inert and can be regarded as harmless
- Static - Polythene can acquire static electrical charges. Sparks are potentially dangerous in areas where flame or explosion hazards exist.
- Skin Contact - No special measures
- Eye contact - No special measures
- Inhalation - No special measures
- ingestion - No special measures

## Fire Resistance

### Extinguishing media

- Use Dry Powder

### Unsuitable Extinguishing

- Do not use direct water jets in the early stages of extinguishing a fire as this may help to spread the flames. Do Not use water extinguishers in close proximity to live electrical installations.

### Fire fighting

- Seek advice from local Fire Authority



## Disposal Of Product

- Through normal trade waste outlets. F Mercer & Sons are a fully licensed Re-cycler and will recycle any polythene in line with the department of environment guidelines and standards.

