

Declaration of Performance

Unique identification code of the product-type:

1.	Product name	Colour	Thickness
	Visqueen R400 Radon Membrane	Red	400 micron

2.	Intended use	for damp proofing in buildings
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)	Visqueen Maerdy Industrial Estate Rhymney, UK, NP22 5PY
4.	Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):	Not relevant
5.	System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 2+
6.	a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13967:2017
	Notified body/ies	British Board of Agrément 0836 SGS Italia 1381
6	b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued	Not relevant

7. Declaration performance

7	Essential Characteristics	Performance	Harmonised Technical Specification
	Reaction to Fire	F	EN 13967:2017
	Water tightness	Pass	
	Resistance to Impact	≥200mm	
	Resistance to static loading	20Kg	
	Durability against heat ageing	Pass	
	Durability against chemicals	Pass	

To view all test results, refer to Visqueen R400 Radon Membrane datasheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Place

Signature

Date

Derbyshire, UK



21/12/2020

Cameron Yates
Technical Product Manager