



DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) no 305/2011

No: DOP 2022 – AR124501

1. Unique identification code of the product

Arbothane 1245. For Batch number see product packaging

2. Intended uses/es

EN15651 -1: 2012 Sealants for façade elements

3. Supplier

Adshead Ratcliffe & Co Ltd, Derby Road, Belper, Derby, DE56 1WJ

4. Authorised Representative

Not Applicable

5. System of AVCP

System 3

6. Designated Standard

The Approved Body 4ward Testing, Identification Number 2538, performed initial type testing and issued a test report to EN 15651: 2012, Pt 1: Sealants for façade elements.

7. Declared Performance

Substrate: mortar with Arbokol AG2 Porous primer
Conditioning A where appropriate



Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	NPD	EN15651-1:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness as determined by:-		
Resistance to Flow (ISO 7390)	≤ 3 mm	
Loss of Volume (ISO 10563)	≤ 10 %	
Determination of Tensile Properties at Maintained Extension (ISO 8340)	Pass (23°C)	
	Pass (-20°C)	
Durability	NPD	
Determination of Tensile Properties at Maintained Extension after Water Immersion (ISO 10590)	Pass	

8. Appropriate Technical Documentation for which a European Technical Assessment has been issued

Not Applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

A handwritten signature in black ink, appearing to read 'a. Crawford', with a stylized flourish at the end.

Adam Crawford
Technical Services Manager

Belper (UK), 04 August 2022