

Always. Reliable. Tight.

Tundish

AT110

Article no.: 0827001601, GTIN: 4052487171663



- **With axial tolerance compensation**
- **Adhesive ribbon for simple integration of vapour barrier foil**
- **Non-trip installation according to DGUV 38 §12a thanks to step safe insert**
- **With integrated level for position alignment of the tundish**

Tundish with integrated step protection insert for setting base slab in concrete for optimum sealing to the underground sewer pipe. To compensate an offset (after concreting) between downpipe and base drain in any direction.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Saves rectangular recesses and therefore complex follow-up work
- Simple on-site installation
- Gas-tight and watertight connection to the base slab thanks to the integrated 3-ribbed seal
- TPE sealing lips to seal underground sewage pipe
- Step safe insert with perforation and dirt trap grooves can be used during construction to drain the base slab
- Undercut for optimum fixing in concrete

Scope of delivery:

- Clamping strap
- Step safe insert

Dimensions:

- Diameter 385 mm
- for underground sewage pipe \varnothing 110 mm

Properties:

- Built-in stop in tundish for exact pipe positioning

Material:

- Step safe insert: PP
- Funnel: ABS/TPE

Tightness:

- Gas-tight and watertight
- Radon-tight

Tests/Standards:

- KG 2000 pipes to DIN EN 14758
- KG pipes to DIN EN 13476-2

FEATURES

Carrier pipe \varnothing_a 110
(mm):
Packing unit (pieces): 1

PICTURES

