

## Visqueen HP Tanking Primer, 5L

### Features and benefits

- No mixing required - use straight from the tin
- Rapid cure - quick and easy to install in one coat application

### Product description

Visqueen HP (High Performance) Tanking Primer is a black elastomeric bituminous priming solution. The product is supplied in a 5 litre tin.

### Approvals and standards

- BBA Certified with Visqueen Self Adhesive Membrane, Visqueen Gas Resistant Self Adhesive Membrane and Visqueen TorchOn Tanking Membrane.
- Quality Management System ISO 9001:2015


### Usage

The primer can be used to prepare a variety of substrates including concrete, metal and masonry. It significantly improves the bond of the applied membrane.

It is designed to prepare surfaces prior to the applications of Visqueen self adhesive membranes and Visqueen TorchOn Tanking Membrane.

### System components

#### Find your local stockist



## Visqueen HP Tanking Primer, 5L

### Storage and handling

Store in an upright position, under cover and away from frost. Keep only in original container, in a cool, well ventilated space, away from heat sources. Keep the container closed when not in use.

---

### Preparation

Inspect concrete surfaces for honeycombed areas and holes, if required bag-rub any irregularities or fill the surface with a suitable filler such as 3:1 mortar mix. All surfaces should be frost free, dry, smooth, clean, and free from oils, grease, condensation and other contamination. Remove areas of laitance.

Concrete substrates must be cured for a minimum 7 days prior to primer application.

---

### Installation

Visqueen HP Tanking Primer can be applied directly from the tin using a brush, or transferred to another suitable container and then applied by roller. Do not pour directly onto the surface.

Apply 1 coat of Visqueen HP Tanking Primer at a coverage of 6/8m<sup>2</sup> per litre depending on the porosity of the surface. The primer will dry in 2-8 hours depending upon temperature and the primer should be covered by the membrane within 24 hours.

---

### Usable temperature range

It is recommended that Visqueen HP Tanking Primer is used above 5°C.

---

### Additional information

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

### Health and safety information

Refer to Visqueen HP Tanking Primer material safety datasheet (MSDS).

## Visqueen HP Tanking Primer, 5L

### About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website ([www.visqueen.com](http://www.visqueen.com)) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or [enquiries@visqueen.com](mailto:enquiries@visqueen.com)

### Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

### Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

### Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

### Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

### Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.