



## DECLARATION OF PERFORMANCE

**Product for Protection and repair of concrete structures  
U(S1) W(1) (2/3/4) (5/40)**

1. Unique identification code of the product-type:

**TEKINJECT PU 1C HYDRO**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of EU Construction Products Regulation No. 305/2011:  
Batch number are unique and enable the product to be traced as required by system 4 and also to verify consistency of performance
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Swelling fitted fillings of cracks, voids and interstices in concrete (Category S) , according to EN 1504-5**

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):  
TEKINJECT BV  
Kruisblok 6  
2320 Hoogstraten  
Email: info@tekinject.com
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): NOT APPLICABLE
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**EN 1504-5:2014 : System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: Not applicable



8. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Watertightness, EN 14068 (crack conditioning) without movement in concrete	$\geq 2 \times 10^5$ Pa No water Leak	EN 1504-5 :2014
Compatibility with Concrete	Weight variation reach a constant level before 28 days 8,80%	
Determination of potlife: Bond strength EN ISO 9514 and EN 1542	Temperature 10°C Initial :0,17Mpa	
	Temperature 23 °C Initial: 0,22Mpa	
	Temperature 30°C Initial 0,25Mpa	
Volume changes of injection products after air drying and water storages cycles, EN 14498 and EN 1504-5 Table 3c n°6/7	<u>Condition A</u> Constant expansion level at 72h	
	<u>Condition B</u> 0% variation	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

On the behalf of the manufacturer by Guy Janssen, Quality Manager

TEKINJECT BV  
 Kruisblok 6 - 2320 Hoogstraten - Belgium  
 info@tekinject.com  
 VAT: BE0800.171.410.