



ARDITEX NA NO ALTERNATIVE



the original yellow bag®



In the 1970s ARDEX launched the original **ARDITEX**, and for over 40 years the **ARDITEX** range of levelling compounds has offered the professional flooring contractor unique application and performance benefits to help minimise installation risk.

In 2006 ARDEX launched the next generation of levelling compounds, **ARDITEX NA**, which, like its predecessor, reduces the need for intensive preparation and priming, saving the professional flooring contractor both time and money, as well as offering a number of unique additional benefits.

ARDITEX NA

the original yellow bag®

With a long history that includes thousands of successful installations, from small domestic refurbishments, to the largest tower in the world, The Burj Khalifa in Dubai, contractors have been levelling subfloors with ARDITEX NA for years, under the most demanding site conditions.



REDUCES THE NEED FOR EXPENSIVE PREPARATION AND PRIMING | EXCELLENT ADHESION TO ALMOST ALL SUBSTRATES WITHOUT PRIMING: FLOORING GRADE PLYWOOD, BITUMEN ADHESIVE RESIDUES, GLAZED AND UNGLAZED CERAMIC TILES, QUARRY TILES, STEEL, FLOORING GRADE ASPHALT, ADHESIVE RESIDUES | UNAFFECTED BY MOISTURE | CAN BE USED UNDER AN ARDEX DAMP PROOF MEMBRANE, ARDEX MVS 95 MOISTURE VAPOUR SUPPRESSANT AND EVEN DIRECT TO DAMP CONCRETE | EXCELLENT FLOW, AS SMOOTH AS A WATER MIX | WALK ON IN 2 HOURS | APPLY RESILIENT FLOORCOVERINGS AFTER ONLY 4 HOURS AND CERAMIC TILES AFTER 3 HOURS | CAN BE APPLIED UP TO 30mm WITH THE INCLUSION OF ARDEX COARSE AGGREGATE | ULTRA RAPID SETTING EVEN AT THICKER APPLICATIONS | ADVANCED PERFORMANCE, EVEN AT LOWER TEMPERATURES | 5m² COVERAGE AT 3mm | SUITABLE FOR USE ON FLOORS WITH UNDERFLOOR HEATING | CAN BE USED TO ENCAPSULATE UNDER-TILE HEATING CABLES | MARINE APPROVED | LOW ODOUR AND PROTEIN FREE.



the original yellow bag®

ARDITEX NA applied direct to a damp subfloor without priming

- Moisture tolerant - can be used under an ARDEX Damp Proof Membrane
- Pre-smoothing maximises the coverage and application properties of the ARDEX DPM



the original yellow bag®

ARDITEX NA applied direct to ARDEX MVS 95 without priming

- The ultimate fast track system for controlling residual construction moisture
- Suitable for use on floors with underfloor heating

THE ULTIMATE SYSTEM FOR THE INSTALLATION OF LUXURY VINYL TILES

1 MOISTURE CONTROL

2 LEVELLING AND SMOOTHING

3 FLOORCOVERING ADHESIVE

ARDEX high performance flooring products are designed to work together for total peace of mind, and are backed up by unparalleled technical and field support.

Moisture Controlled – Guaranteed Fast Track Solutions from ARDEX, The Moisture Control Experts.

Many problems which occur with floorcoverings are as a result of moisture in the subfloor, so it is essential that the final floorcovering is protected from the passage of moisture from below. Prior to the installation of floorcoverings, it is important to identify the type and level of moisture present in the subfloor, which usually results from either rising damp, or residual construction moisture.

WHEN TO USE ARDEX DPM 1 C / ARDEX DPM 1 C R

WHERE MOISTURE READINGS EXCEED 95% RH (UP TO 98% RH)

TO PROTECT THE FINAL FLOORCOVERING FROM GROUND BEARING MOISTURE

WHERE THERE IS NO FUNCTIONING STRUCTURAL DAMP PROOF MEMBRANE OR WHERE IT MAY HAVE BEEN DAMAGED IN THE CONSTRUCTION PROCESS

ARDEX Damp Proof Membranes protect the final floorcovering from both ground bearing, and residual construction moisture, and can be used where there is no functioning structural damp proof membrane present.



WHEN TO USE ARDEX MVS 95

WHERE A STRUCTURAL DAMP PROOF MEMBRANE IS PRESENT AND EFFECTIVE

WHERE MOISTURE READINGS ARE BELOW 95% RH

TO SUPPRESS RESIDUAL CONSTRUCTION MOISTURE AND SPEED UP THE INSTALLATION PROCESS

ARDEX MVS 95 Moisture Vapour Suppressant protects the final floorcovering from residual construction moisture, ensuring fast track flooring installations.



1

2

3

ARDEX AF 175 Luxury Vinyl Tile Adhesive

- Fibre reinforced to offer the following benefits:
 - Minimises lateral movement during installation
 - Eliminates adhesive squeeze between tiles and planks
 - Improved indentation resistance
- Install tiles and planks after just 5 minutes
- Walk on after 2 hours
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 48m²



ARDEX AF 175 is the ideal adhesive for securing Luxury Vinyl Tiles and Planks.



ARDITEX NA applied direct to ARDEX DPM 1 C without priming

- The ultimate moisture control system – ARDEX DPM 1 C is ideal for damp floors with no functioning structural DPM
- ARDITEX NA is walkable in 2 hours



the original yellow bag®



ARDITEX NA applied direct to bitumen adhesive residues without priming

- Ideal for use after the removal of old parquet floors
- Can be laid up to 30mm, in a single application, with the inclusion of ARDEX Coarse Aggregate



the original yellow bag®



the original yellow bag

ARDITEX NA applied direct to flooring grade plywood without priming

- Can be applied from a feather edge up to 6mm
- Ready to receive floorcoverings in as little as 4 hours



the original yellow bag

ARDITEX NA applied direct to ceramic tiles without priming

- No abrading or grinding required on degreased tiles
- Can be applied up 12mm neat



the original yellow bag®

REDUCES THE NEED FOR EXPENSIVE PREPARATION AND PRIMING | EXCELLENT ADHESION TO ALMOST ALL SUBSTRATES WITHOUT PRIMING: FLOORING GRADE PLYWOOD, BITUMEN ADHESIVE RESIDUES, GLAZED AND UNGLAZED CERAMIC TILES, QUARRY TILES, STEEL, FLOORING GRADE ASPHALT, ADHESIVE RESIDUES | UNAFFECTED BY MOISTURE | CAN BE USED UNDER AN ARDEX DAMP PROOF MEMBRANE, ARDEX MVS 95 MOISTURE VAPOUR SUPPRESSANT AND EVEN DIRECT TO DAMP CONCRETE | EXCELLENT FLOW, AS SMOOTH AS A WATER MIX | WALK ON IN 2 HOURS | APPLY RESILIENT FLOORCOVERINGS AFTER ONLY 4 HOURS AND CERAMIC TILES AFTER 3 HOURS | CAN BE APPLIED UP TO 30mm WITH THE INCLUSION OF ARDEX COARSE AGGREGATE | ULTRA RAPID SETTING EVEN AT THICKER APPLICATIONS | ADVANCED PERFORMANCE, EVEN AT LOWER TEMPERATURES | 5m² COVERAGE AT 3mm | SUITABLE FOR USE ON FLOORS WITH UNDERFLOOR HEATING | CAN BE USED TO ENCAPSULATE UNDER-TILE HEATING CABLES | MARINE APPROVED | LOW ODOUR AND PROTEIN FREE.



ARDEX UK Limited
01440 714939

X @ARDEXUKFlooring
info@ardex.co.uk

f ARDEX UK
www.ardex.co.uk

in ARDEX UK