

# Sustainability data sheet

## ARDEX FEATHER FINISH

### Rapid Drying Patching and Smoothing Compound

Install floorcoverings after 15 minutes

No priming required

Excellent coverage - up to 50m<sup>2</sup> per bag

#### Emissions

According GEV (Gemeinschaft  
Emissionskontrollierte  
Verlegewerkstoffe, Klebstoffe und  
Bauprodukte e.V., Düsseldorf)

**EMICODE® EC 1<sup>PLUS</sup>,**  
very low emission



solvent-free

#### EPD (Environmental Product Declaration)

ARDEX FEATHER FINISH corresponds to FEICA  
EPD:

**EPD-DBC-20220218-IBF1-EN**

#### Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE ZP1** - cementitious product, low-chromate

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)



# ARDEX FEATHER FINISH

Rapid Drying Patching and Smoothing Compound

## Sustainable Building

### Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

#### Version 2018

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX FEATHER FINISH can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX FEATHER FINISH has the GISCODE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX FEATHER FINISH fulfills the requirements for highest Quality Level 4.**

#### Version 2015

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX FEATHER FINISH can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX FEATHER FINISH is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX FEATHER FINISH fulfills the requirements for highest Quality Level 4.**

### Accordinging LEED (Leadership in Energy and Environmental Design)

#### Version 4 (2014)

##### EQ: Low Emitting Materials

ARDEX FEATHER FINISH meets the requirements according EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV which are accepted by LEED.

**ARDEX FEATHER FINISH meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.**

##### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX FEATHER FINISH corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX FEATHER FINISH fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

#### Version 2009

##### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

Cement based filling compound are not directly described by LEED. But the permitted limit value in the category coatings is 50 g/L. The VOC value of ARDEX FEATHER FINISH is < 50 g/L.

**ARDEX FEATHER FINISH meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

##### MR Credit 5.1 und 5.2: Regional Materials

###### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
www.ardex.de

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
kundendienst@ardex.de  
www.ardex.de



# ARDEX FEATHER FINISH

Rapid Drying Patching and Smoothing Compound

## Sustainable Building

According BREEAM (Building Research Establishment Environmental Assessment Methodology)

### Version 2016

#### BREEAM criteria Hea 02 Indoor air quality

ARDEX FEATHER FINISH can be classified as Flooring materials (including floor levelling compounds and resin flooring). ARDEX FEATHER FINISH meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX FEATHER FINISH is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX FEATHER FINISH meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.**

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 09/03/2023

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

